

## FORTICO SEALER

A filling, water-based one component primer for roller application. FORTICO SEALER can be used as a primer for parquet to finish with waterborne finishes from the FORTICO range of products. FORTICO SEALER is recommended for floor heating, exotic wood types and cork.

- » Prevents side-bonding effect and minimizes roughening of the fibre.
- » Recommended for tropical wood species and for places with floor heating.

### TECHNICAL DATA

**Product type**  
waterborne

**Cleaning**  
water

**Viscosity**  
+/- 30 sec - DIN 4 mm

**Solid content**  
+/- 35%

**Coverage**  
8-12 m<sup>2</sup>/liter per coat

**Drying times**  
dust dry: after 20 to 30 minutes  
sandable: after 2 to 3 hours

**Sanding grit**  
P 120-150

**Storage/transport**  
between 5°C and 25°C

**Disposal**  
dispose of residue and empty packaging in accordance with local ordinances.



1L

5L



### PREPARATION

Make sure that all old finish coats are completely removed and that the wood is free from dust and other dirt. Sanding using the correct method : deep sanding with 60-80-100 grit then sanding with 100 grit. Can be used on sanded, planed, and brushed wood.

### APPLICATION

Stir and shake well before use. Apply generously with a roller or brush.

### FINISHING

Finish FORTICO SEALER with a waterborne finish from the FORTICO product line.

### IMPORTANT INFORMATION ▲

Only use non-corrosive materials. Clean all materials with water immediately after use. For exotic types of wood, the finishing should be tested in advance. For industrial application, please consult Ciranova® technical support. **Water-based products can develop skins after contact with air. Filter beforehand, if necessary.**