

## OCULTO PLUS

OCULTO PLUS is an invisible, 35% Bio-based, environmentally friendly, water-based PU impregnating oil for parquet and wooden furniture. The wood will have a slightly intense and ultra matte appearance. OCULTO PLUS is non-yellowing and has anti-slip properties.

- » Ultimate invisible finish
- » Slightly intense appearance
- » Very easy to apply
- » Non-yellowing

### TECHNICAL DATA

**Product type**  
waterborne

**Cleaning**  
Water

**Gloss level**  
Invisible

**Viscosity**  
+/-25 sec - DIN 4mm

**Solids content**  
+/- 31%

**Packaging**  
6 x 1 L  
4 x 5 L

**Coverage**  
10-12m<sup>2</sup>/liter per coat  
125-150 sq.ft./L per coat  
470 - 560 sq.ft./gal

**Drying times**  
Dust dry: after 20 to 30 minutes  
Sandable: after 4 to 6 hours  
Lightly walkable: after 24 hours  
Fully cured: After +/- 7 days

**Sanding grit**  
P 120-150

**Storage/transport**  
between 5°C and 25°C

**Disposal**  
Dispose of residue and empty packaging in accordance with local ordinances.



### PREPARATION

Make sure all prior coatings are completely removed and the wood surface is free from dust and other contamination. Sanding using the correct method: deep sanding with 60-80-100 grit then sanding with 100 grit. Can be used on sanded, planed and brushed wood.

### APPLICATION

OCULTO PLUS can be used both as primer and as finishing coat. It can be applied in three coats. Stir thoroughly before use and do not dilute. Apply the product using a roller, brush or spray gun. A short-pile roller is recommended (microfiber 4-6mm). Contact Ciranova® technical support for spray application. Apply the first coat in the direction of the wood. After 4-6 hours, apply a second coat in the same way as the first coat. Let dry for 12-24 hours and afterwards do an intermediate sanding using grit 180-220, then apply the third coat. Optional : a hardener can be added.

### DRYING TIMES

Dust dry: after 20 to 30 minutes  
Sandable: after 4 to 6 hours  
Lightly walkable: after 24 hours  
Fully cured: After +/- 7 days

### FINISHING

OCULTO PLUS can be used both as primer and as a finishing coat.

### MAINTENANCE

Regular maintenance with Ciranova® Hard Floor Fresh. Use UNICARE X-MATT for periodic maintenance. Ciranova® Hard

### IMPORTANT INFORMATION ⚠

Only use non-corrosive materials. Clean all materials with water immediately after use. If the wood needs to be stained first, only use Ciranova® Aquapad + 10% Aquapad Hardener. For exotic types of wood, the finishing should be tested in advance. For industrial application, please consult Ciranova® technical support. Water-based products can develop skins after contact with air. Filter beforehand, if necessary.