

## UNICARE X-MATT

Universal maintenance product that provides an extra protective layer to all types of MATTE floors. UNICARE X-MATT can also be used on laminate, LVT and on our matte waterborne finishes like FORTICO, ECOFIX PLUS & OCULTO PLUS. UNICARE X-MATT provides an extra protective film and hides micro-scratches, maintaining the original look of the floor. The extra matte protection ensures that the finishing layer is maintained longer and prevents dirt becoming ingrained.

- » Extra protection layer for all types of MATTE waterborne finishes.
- » Can also be used on laminate, LVT and matte varnished floors.
- » Hides micro-scratches and restores the original look of the floor.

### TECHNICAL DATA

**Product type**  
waterborne

**Cleaning**  
Water

**Mixing ratio**  
Use undiluted

**Gloss level**  
Extra matte

**PH**  
8

**Packaging**  
6 x 750 ml

**Coverage**  
60 - 80 m<sup>2</sup>/liter  
650-850 sq.ft./L  
2460 - 3220 sq.ft./gal

**Drying times**  
1 hour at room temperature

**Storage/transport**  
between 5°C and 25°C

**Disposal**  
Dispose of residue and empty packaging in accordance with local ordinances.



0,75L

### PREPARATION

Ensure that the floor is clean before applying UNICARE X-MATT. To this end, you can first clean the wood with Ciranova® Hard floor Fresh. Apply the UNICARE X-MATT to a dry and grease-free surface.

### APPLICATION

Use the UNICARE X-MATT undiluted. Apply the UNICARE X-MATT evenly with a microfiber cloth or mop, in the direction of the wood grain. If necessary, you can apply a second layer of UNICARE X-MATT after 1 hour.

### CAUTION

+/- 1 hour, depending on the amount applied, the surrounding temperature, the humidity and ventilation.

### MAINTENANCE

For regular maintenance of varnished floors and floors treated with UNICARE X-MATT, use Ciranova® Hard Floor Fresh. For removing old layers of UNICARE X-MATT, use Ciranova® Hard Floor Cleaner.