

WOOD FILLER GEL

WOOD FILLER GEL is a gel that should be mixed with fine sanding dust of the wood to be treated. For stopping nail holes, wood parquet floors and various small wood repairs. For larger repairs, you can repeat the treatment. This product has limited shrinkage.

- » Binding agent to mix with the sanding dust.
- » To quickly plug nail holes, gnarls and seems.
- » Takes on the color of the stain and oil.



EXTRA

INDOOR

1L

5L



APPLICATION

Mix the WOOD FILLER GEL with fine sanding dust (P100 - P120) of the wood type to be treated. Sanding using the correct method : deep sanding with 60-80-100 grit then sanding with 100 grit. It is difficult to provide a correct ratio, as it depends on the application. The WOOD FILLER GEL works only as a binding agent, meaning you will be using more sanding dust than WOOD FILLER GEL. Apply the wood paste with a spatula or putty knife. Store the paste in a closed jar to prevent hardening.

FINISHING

Sand smooth with grain P 100 after drying.

TECHNICAL DATA

Product type

solvent-based

Mixing ratio

depending on the application

Number of colors

colorless

Drying times

sandable after: 1 hours

Storage/transport

between 5°C and 25°C

Disposal

dispose of residue and empty packaging in accordance with local ordinances.