

AQUAVINTAGE 2C

PRODUCT DESCRIPTION:

Water based reactive stain, specially fit for ageing the wood in a simple and fast way. Can also react on wood that is not containing tannin.

RANGE OF APPLICATION:

Industrial application for Wood Flooring and wood panels.
Only for interior use

TECHNICAL DATA

extra component:	ACTIVATOR AQUAVINTAGE 2C
mixing ratio:	50:50
pot-life:	ca 3 weeks
density:	+/- 1.00 KG/L
viscosity:	as water
colors:	8 COLORS AVAILABLE
solid content:	-
gloss:	-
thinner:	-
coverage per coat:	ca 50g/m ²
Coverage USA per coat:	ca 5 g/ft ²
drying:	Reaction time: minimum 12 hrs

APPLICATION MATERIAL



PACKING

5lt

APPLICATION

preparation substrate: Prepare the wood according the rules of the art and remove the sanding dust carefully

processing: Mix the Aquavintage 2C with the Activator 1/1. During the application of the stain, stirr regularly.

- Stirr well before use.
- Spraying : apply +/- 50g/m², even outing with a brush.
- Manual application : apply the Aquavintage 2C ca 50g/m² with a brush in the direction of the wood fiber, even outing afterwards with a brush.

PROTECTION

After respecting the reaction time, it is recommended to apply 1 coat of Ecofix or Oculito to block the color before protecting with an oil or a lacquer.

IMPORTANT INFORMATION

- Respect reaction time.
- The final color depends on the type of wood, sanding, wood preparation and the applied quantity. For this reason its always recommended to make a test first before starting production.
- Only use stainless material.
- Clean all material immediately after use.

SHELF-LIFE

In well-closed and original packing: minimum 12 months

WAREHOUSING

by 10 – 40 °C

CLEANING

HYDRO CLEANER 7984

ATTENTION ⚠

"All tests and application methods are done with the above-mentioned Debal Coatings components. We are not responsible for application with other materials, unless written agreement from Debal Coatings"