

ATOLL DUST

PRODUCT DESCRIPTION:

ATOLL DUST is a special powder that gives a rustical liming effect.

RANGE OF APPLICATION:

Industrial application for Wood Flooring and wood panels.
Only for interior use

TECHNICAL DATA

extra component:	-
mixing ratio:	optional 10% - 20% in water
pot-life:	-
density:	2.9 KG/L
viscosity:	-
colors:	off white
solid content:	100%
gloss:	-
thinner:	water
coverage per coat:	depending on the effect to achieve
Coverage USA per coat:	depending on the effect to achieve
drying:	3hrs - 4hrs at room temperature. Forced drying possible.

APPLICATION MATERIAL



PACKING

5kg - 20kg



APPLICATION

preparation substrate: Prepare the wood well by sanding or brushing. Brush the woodgrains carefully, remove the dust. Apply Atoll dust on rough prepared wood or stained wood.

processing: Mix 100:10 Atoll dust with water. Stir well, spray the surface approx. 50gr/m². Dry on room temperature or dry with hot air oven. For heavy atoll dust effect, rub up dry Atoll dust with a cloth or pad. Remove the excess of Atoll dust.

PROTECTION

UV oil or Hardwax oil Magic finish.
For UV oil finish seal first the atoll dust surface with Ecofix or Oculito.

SHELF-LIFE

In well-closed and original packing: minimum 24 months

WAREHOUSING

by 10 - 40 °C

CLEANING

-

ATTENTION ⚠

"All tests and application methods are done with the above-mentioned Debal Coatings components. We are not responsible for application with other materials, unless written agreement from Debal Coatings"