

ECOFIX WOODLOOK

PRODUCT DESCRIPTION:

ECOFIX WOODLOOK is a waterbased ecological impregnating oil for parquet and wooden furniture. The wood maintains is slightly bleaching. To be used as a primer.

RANGE OF APPLICATION:

Industrial application for Wood Flooring and wood panels.
Only for interior use

TECHNICAL DATA

extra component:	-
mixing ratio:	-
pot-life:	-
density:	ca 1.02 KG/L
viscosity:	ca 20 sec. DIN 4 20°C
colors:	Milky
solid content:	ca 26%
gloss:	CA 15 Gu at 60°
thinner:	water
coverage per coat:	ca 50g/m ²
Coverage USA per coat:	ca 5g/ ft ²
drying:	3hrs – 4hrs at room temperature. Forced drying possible.

APPLICATION MATERIAL



PACKING

5lt -25lt

APPLICATION

preparation substrate:	Prepare the wood according the rules of the art and remove the sanding dust carefully
processing:	- stirr well before use. - stain the wood if required with REACTIVE STAINS or waterbased stains. - application quantity : ca 50 - 60g/ m ²

PROTECTION

Natural Oils, UV Oils, Lacquers

IMPORTANT INFORMATION

Ecofix Woodlook skins fast in contact with air, if necessary filter before use.
- it is recommended to first make a test on the wood before starting the production.
- be aware of discoloration or delamination because of the substances in the wood or special wood species.
- use only stainless material.
- After use, rinse the material directly with Hydro Cleaner and water.

SHELF-LIFE

In well-closed and original packing: minimum 12 months

WAREHOUSING

by 10 – 40 °C

CLEANING

HYDRO CLEANER 7984

ATTENTION ⚠

"All tests and application methods are done with the above-mentioned Debal Coatings components. We are not responsible for application with other materials, unless written agreement from Debal Coatings"