

## UN1CO

### PRODUCT DESCRIPTION:

UN1CO is a 2 component, 1-coat oil from the newest generation using renewable natural raw materials. Thanks to its special technology there is only one coat needed to finish your parquet. The combination of the oil with the hardener results in a fast drying and excellent chemical and mechanical resistant finish. UN1CO is VOC and Cobalt free.

### RANGE OF APPLICATION:

Industrial application for Wood Flooring and wood panels. Only for interior use

### CERTIFICATES/LABELS:

Indoor Air confort GOLD / EN13501 B fl s1

### TECHNICAL DATA

<b>extra component:</b>	HARDENER UN1CO
<b>mixing ratio:</b>	100:30
<b>pot-life:</b>	CA 3 HRS
<b>density:</b>	depending on color
<b>viscosity:</b>	ca 40 sec DIN 4 (at 20°C)
<b>colors:</b>	16 colors available
<b>solid content:</b>	ca 100%
<b>gloss:</b>	matt - depending on the applied quantity
<b>thinner:</b>	-
<b>coverage per coat:</b>	ca 15 - 20g/m <sup>2</sup>
<b>Coverage USA per coat:</b>	ca 1.5 - 2g/ft <sup>2</sup>
<b>drying:</b>	ca 24 hrs at room temperature. Depending on air circulation and temperatures.

### APPLICATION MATERIAL



### PACKING

1lt - 20lt

### APPLICATION

- preparation substrate:** Prepare the wood according the rules of the art and remove the sanding dust carefully
- processing:** Mix the oil with the hardener (100/30) and let the product rest for about 10 minutes.  
When needed color the wood with stains from Ciranova Industrial Finishes.  
UN1CO can be applied with a roller coater and buf after with a white or beige pad. Use brushes to remove the marks of the buffing pads.

### MAINTENANCE

Please consult the maintenance programm from Ciranova.

### IMPORTANT INFORMATION

Used cloths or pads should be plunged in water because of the danger of spontaneous combustion. Colored Hardwaxoils should always be tested before treating the entire surface. Used sanding grain, type of wood, ..... may affect the final color.

### SHELF-LIFE

In well-closed and original packing: minimum 12 months

### WAREHOUSING

by 10 - 40 °C

### CLEANING

COMBI CLEANER 2879

### ATTENTION ⚠

"All tests and application methods are done with the above-mentioned Debal Coatings components. We are not responsible for application with other materials, unless written agreement from Debal Coatings"